

Enterprise Capacity 3.5 HDD (Helium)

VERSION 7

Channel Data Sheet

Maximum Storage Capacity for Highest Rack Space Efficiency

- 12TB per drive¹ for 50% more petabytes per rack²
- Industry's lowest power and weight for optimum data center TCO
- Highest 12TB HDD performance with enhanced caching, making it perfect for Big Data applications
- Hyperscale SATA model tuned for large data transfers
- PowerBalance™ feature optimizes IOPS/Watt
- Advanced Write Caching feature for 20% boost in random write performance²
- Forged, wrought-aluminum base and a helium sealed-drive design with no porosity and uniform density
- Superior material and weld-width design for a more robust, hermetically sealed-drive enclosure that protects from helium leaks
- Digital environmental sensors for measuring internal pressure, helping to ensure high reliability, performance and quality
- Latest hermetic interconnect technology supporting higher data rate heads and higher pin counts for extreme thermal conditions
- Proven enterprise-class reliability backed by 2.5M-hr MTBF



Best-Fit Applications

- Hyperscale applications/cloud data centers
- Massive scale-out data centers
- Big Data applications
- High-capacity density RAID storage
- Mainstream enterprise external storage arrays
- Distributed file systems, including Hadoop and Ceph
- Enterprise backup and restore—D2D, virtual tape
- Centralized surveillance

¹ Seagate recommends validating your configuration with your HBA/RAID controller manufacturer to ensure full capacity capabilities.

² Compared to 8TB competitive product.



Enterprise Capacity 3.5 HDD (Helium)



VERSION 7

Specifications	SATA 6Gb/s	12Gb/s SAS
Capacity	12TB	12TB
Standard Model (512e)	ST12000NM0007	ST12000NM0027
Standard Model (4Kn)	ST12000NM0047	ST12000NM0067
SED Model (4Kn) ¹	ST12000NM0057	ST12000NM0077
SED Model (512e) ¹	ST12000NM0017	ST12000NM0037
SED-FIPS Model (4Kn) ^{1, 2}	ST12000NM0157	ST12000NM0167
SED-FIPS Model (512e) ^{1, 2}	ST12000NM0137	ST12000NM0147
Features		
Superior Helium Sealed-Drive Design With Wide Weld	Yes	Yes
Digital Sensors for Helium Pressure	Yes	Yes
Protection Information (T10 DIF)	—	Yes
SuperParity	Yes	Yes
PowerChoice™/PowerBalance™ Technology	Yes	Yes
Low Halogen/Hot-Plug Support ³	Yes	Yes
Cache, Multisegmented (MB)	256	256
Organic Solderability Preservative	Yes	Yes
Secure Download and Diagnostics (SD&D) RSA 2048 signed firmware	Yes	Yes
Reliability/Data Integrity		
Mean Time Between Failures (MTBF, hours)	2.5 Million	2.5 Million
Reliability Rating @ Full 24x7 Operation (AFR)	0.35%	0.35%
Nonrecoverable Read Errors per Bits Read	1 sector per 10E15	1 sector per 10E15
Power-On Hours per Year (24x7)	8760	8760
512e Sector Size (Bytes per Sector)	512	512, 520, 528
4Kn Sector Size (Bytes per Sector)	4096	4096, 4160, 4224
Limited Warranty (years)	5	5
Performance		
Spindle Speed (RPM)	7200	7200
Interface Access Speed (Gb/s)	6.0, 3.0	12.0, 6.0, 3.0
Max. Sustained Transfer Rate OD (MB/s, MiB/s)	Up to 261, 249	Up to 261, 249
Random Read/Write 4K QD16 WCD (IOPS)	170/400	170/400
Interface Ports	Single	Dual
Rotational Vibration @ 1500Hz (rad/s ²)	12.5	12.5
Power Consumption		
Idle A (W) Average	5.0W	5.5W
Average Latency (ms)	4.16	4.16
Operating Power ⁴	7.8	9.3
Power Supply Requirements	+12 V and +5 V	+12 V and +5 V
Environmental		
Temperature, Operating (°C)	5°C – 60°C	5°C – 60°C
Vibration, Nonoperating: 10Hz to 500Hz (Gms)	2.27	2.27
Physical		
Height (mm/in, max) ⁵	26.11mm/1.028in	26.11mm/1.028in
Width (mm/in, max) ⁵	101.60mm/4.0in	101.60mm/4.0in
Depth (mm/in, max) ⁵	147.0mm/5.787in	147.0mm/5.787in
Weight (g/lb)	650g/1.433lb	650g/1.433lb
Carton Unit Quantity	20	20
Cartons per Pallet / Cartons per Layer	40 / 8	40 / 8

¹ Self-Encrypting Drives (SED) and FIPS 140-2 Validated drives are not available in all models or countries. May require TCG-compliant host or controller support.

² See FIPS 140-2 Level 2 Certificate at: <http://csrc.nist.gov/groups/STM/cmvp/documents/140-1/1401val2011.htm#1635>

³ Supports Hotplug operation per Serial ATA Revision 2.6 specification.

⁴ SATA Random 8K1Q 50% Write/50% Read WCD @ 40 IO/s, SAS Random 4K4Q 50% Write/50% Read WCD @ 165 IO/s

⁵ These base deck dimensions conform to the Small Form Factor Standard (SFF-8301) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8323.

SEAGATE.COM

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000

ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888

EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2017 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. PowerBalance and PowerChoice are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit www.bis.doc.gov), and may be controlled for export, import and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. DS1925.1M-1703US March 2017