sensbi

MINI-WRELEI-NN
Smart Relay Switch

QUICK GUIDE

This manual is for reference only. We advise for installation to be performed by professionals. Please see our website for most detailed instructions. www.sensbi.com

Warning
1. Make sure you have completely cut off the power supply to the wall switch you are working on.
2. Do not install the wall switch with wet hands or when standing on wet surfaces.
3. Do not use beyond maximum load specified on the product.

Installation
As shown in the wiring diagram, insert the wires into the corresponding terminals and screw them in well. Then, put the mini module into the wall box and install the conventional switch panel.

For no neutral Wi-Fi switch/relay an adapter capacitor needs to be paralleled to the load light of L1, otherwise, the device may not work properly. Please install it according to the illustration on the next page.


Diagram 1: For 1 Gang Mini Module

Mini Switch Module

Lin L1 S1 COM

Conventional Switch

L
N

Load of L1   Capacitor

Note: The conventional switch is only connected to S1, S2, COM ports of mini switch module, do not connect it to other wires.

Diagram 2: For 2 Gang Mini Module

Mini Switch Module

Lin L1 L2 S1 S2 COM

Conventional Switch

L
N

Load of L1   Capacitor

Note: The conventional switch is only connected to S1, S2, COM ports of mini switch module, do not connect it to other wires.

Add device to your app

1. Download the Sensbi app, register if necessary, and login to your account.

Sensbi app is available for both iOS and Android OS. Search the name 'SENSBI' in App Store or Google Play Store.

Sensbi app controls all of your smart products!

Available on the App Store

GET IT ON Google Play

---

2. Important note before getting started:
   For Wi-Fi switches, an operating Wi-Fi router is required, Wi-Fi switches support only 2.4GHz Wi-Fi networks.

3. Power up the wall switch, then press and hold the button (for about 5 seconds) until LED blinks and device enters pairing mode. Alternatively, quickly switch the switch panel 10 times, to put the device into pairing mode.

4. Open the Sensbi app > home page, tap the "+" icon in the top right corner of the screen > add device> under add manually section > select Electrical > Switch (Wi-Fi) > Follow Instructions on the screen to successfully complete the setup.

---

5. Smart operation of the device: Inside the app, click "Smart" at the bottom of your screen, then select the "Tap-to-Run" or "Automation" options, follow instructions on screen to access smart settings for the device.

Connect with Third-Party voice control services

In your app, under your profile, you will find a selection of Third-Party Voice Services that you can connect your device to. Follow in app instructions.

Qualified Certification

Model: _ _ _ _ _ _ _ _ _ _
Surveyor: _ _ _ _ _ _ _ _
Date: _ _ _ _ _ _ _ _ _ _

QC PASS 06

Warranty card

Name: _ _ _ _ _ _ _ _ _ _ _
Contact: _ _ _ _ _ _ _ _ _ _
Issue: _ _ _ _ _ _ _ _ _ _ _