



Ringi + Jingi (SBI-1005(A+B))

1080P WiFi Battery Wireless Doorbell and Chime

- ▶ 6700mAh rechargeable batteries
- ▶ PIR human detection
- ▶ Two-way audio (full duplex)
- ▶ 145° wide viewing angle
- ▶ IP65 weatherproof
- ▶ Wireless chime included



Camera

Image Sensor	1/2.9" 2Megapixel CMOS
Effective Pixels	1920(H) x 1080(V)
Shutter	1/20~ 1/10,000s
Min. Illumination	Color 0.1Lux@F2.0, Black/White 0.01Lux@F2.0
IR Distance	Night visibility up to 10m
Day/Night	Auto(ICR)/Color/B&W
WDR	DWDR
Lens&FOV(H/V/D)	2.4mm@F2.0, 120°/64°/145°

Jingi Chime

Power	100~240V AC
Wireless RF connection	433Mhz
Distance	Up to 80m with no obstacles
Volume	Adjustable
Tones	4 preset

Video&Audio

Compression	H.264
Bit Rate	32Kbps~2Mbps
Frame Rate	1~25fps
Dual Stream	Yes
Audio Input/Output	Built-in mic/speaker

Network

Alarm Trigger	Button triggering, PIR detection
Wireless Security	64/128-bit WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
Communication Protocol	HTTP, DHCP, DNS, TCP/IP
Interface Protocol	Private
Wireless	2.4G WIFI (IEEE802.11b/g/n)
Mobile Phone OS	iOS 9 or later, Android 5 or later
Security	AES128
Max. User Access	4

Battery&PIR

Capacity	6700mAh rechargeable Li batteries
Stand-by Current	200-800 μ A (average)
Working Current	150-200 mA (IR off)
Stand-by Time	10 months
Working Time	3 months (10 times wake up per day)
PIR Detection Range	Max. 5m

PIR Angle	100°
-----------	------

General

Operating Temperature	-20 °C to 50 °C
IP Rating	IP65
Power Supply	DC 5V/1A, AC 12~24V
Power Consumption	Max. 2W
Storage	SD card(Max.128GB), Cloud storage
Optional Accessory	Wireless chime Jingi
Dimensions	62 × 41 × 134mm
Net Weight	200g

Sensbi™ All rights reserved.

