DATASHEET sensbi.com



## Sentri (SBI-1003)

1080P WiFi Outdoor Floodlight Camera

- ▶ PIR human detection
- ▶ Siren alarm
- ▶ Motion zone selection
- ► Two-way audio (half-duplex)
- ▶ Light on/off by PIR detection/schedule/manually
- ▶ Supports WebRTC



		***************************************
Camera		
Image Sensor	1/2.9" 2Megapixel CMOS	
Effective Pixels	1920(H) x 1080(V)	
Shutter	1/20~1/10,000s	
Min. Illumination	Color 0.1Lux@F2.0,	
Min. Illumination	Black/White 0.01Lux@F2.0	
IR Distance	Night visibility up to 10m	
Day/Night	Auto(ICR)/Color/B&W	
WDR	DWDR	
Lens&FOV(H/V/D)	2.8mm@F2.0, 98°/53°/120°	
Video&Audio		
Compression	H.264	
Bit Rate	32Kbps~2Mbps	
Frame Rate	1~25fps	
Dual Stream	Yes	
Audio Input/Output	Built-in mic/speaker	
Siren Alarm	120dB	
Network		
Alarm Trigger	PIR detection	
Wireless Security	64/128-bit WPA/WPA2, WPA-PSK/WPA2-PSK, WPS	
Communication Protocol	HTTP, DHCP, DNS, TCP/IP, RTSP	
Interface Protocol	Private	
Wireless	2.4G WIFI (IEEE802.11b/g/n)	
Mobile Phone OS	iOS 9 or later, Android 5 or later	
Security	AES128	
Max. User Access	6	
Light&PIR		
Lamp Power	25W (12.5W x 2)	
Luminous Flux	Max. 2100lm (adjustable)	
Color Temperature	6000K	
Light On/Off	Manually/PIR detection/schedule	
PIR Detection Range	12m	
PIR Angle	120°	
General		
Operating Temperature	-20 °C to 50 °C	
IP Rating	IP65	

AC 100V~240V

Max. 32W

Power Supply
Power Consumption

Storage	SD card(Max.128G), Cloud storage, NVR
Dimensions	151 × 277 × 132mm
Net Weight	640g

Sensbi™ All rights reserved.

